

Specifications

| Key features | DS-3500 | DS-7000 |
|---------------------------------------|---|--|
| Full body metal case | Black | Black |
| Main switch (REC/STOP/PLAY/RWD) | Push buttons | Precision slide switch |
| Device lock function | PIN (4 digits) | |
| Display | Colour TFT display with white LED backlight Resolution: 176 x 220 pixel Size: 34 x 42 mm / 1.3 x 1.7 inch | |
| Battery | Rechargeable Li-ion-battery Up to 21 hours of recording time with one battery charge | |
| Data security | DSS Pro real-time encryption (128/256 bit) | |
| Storage media | Secure Digital (SD, SDHC), up to 32 GB | |
| Internal storage media | 2 GB (micro SD) DSS Pro SP = approx. 306 hours recording time | |
| External storage media | - | 2 GB SD card |
| Recording Formats | | |
| DSS / DSS Pro | Quality play (16 kHz / 28 kbps) Standard play (12 kHz / 13.7 kbps) | |
| PCM (mono / stereo ³) WAV | ✓ | - |
| MP3 | 256kbps, 128kbps | - |
| Professional Speech Processing | | |
| Author IDs | 10 | |
| Dictation tags = worktypes x items | 200 = 20 x 10 | |
| Priority | High / Normal | |
| Verbal comments | ✓ | |
| Text editor | ✓ | |
| Pending | ✓ | |
| File lock | ✓ | |
| Advanced Recording Features | | |
| Voice activated recording (VCVA) | ✓ | |
| Microphone sensitivity | Dictation / Conference | |
| Insert | Only with DSS Pro & DSS | |
| Overwrite | Only with DSS Pro & DSS | |
| Append | Only with DSS Pro & DSS | |
| Partially erase | Only with DSS Pro & DSS | |
| Index | 32 (DSS Pro), 16 (DSS, MP3, WAV) | 32 (DSS Pro), 16 (DSS) |
| Level meter | ✓ | |
| VCVA indicator | ✓ | |
| Folders | Up to 7 (can be renamed) | |
| Hands-free dictation | Optional with Olympus Footswitch RS31, RS28, RS32 | |
| Stand-alone transcription | Optional with Olympus Footswitch RS31, RS28, RS32 | |
| Full-duplex recording | With headphones | |
| Playback | | |
| Speed | Slow / Normal / Fast | |
| Volume level | Adjustable from 0 to 30 | |
| Stationary Operations | | |
| Applicable as PC microphone | ✓ | ✓ |
| Controlling PC application ODMS | ✓ | ✓ |
| Administrative Settings | | |
| Accessibility | Various settings related to user authorisation, e.g. file deletion protection; menu settings | |
| Splash message | Option to set personalised welcome message during start-up | |
| Main button guide | - | Shows current slide switch function on display |
| Alarms | Option to set alarms for particular occasions; beeping noise | |
| Customisable display content | Option to customise information shown on display | |
| Programmable buttons | 3 | |
| Extended security features | PIN Code Device Lock File Encryption Erase Lock | |

| Administrative Settings | DS-3500 | DS-7000 |
|---|--|--|
| Single user installation | ✓ | ✓ |
| Workgroup installation | ✓ | ✓ |
| Server installations including licence manager and manager tools (optional) | ✓ | ✓ |
| Citrix / WTS support | ✓ | ✓ |
| Thin client support | ✓ | ✓ |
| Technical Data | | |
| Product dimensions (H×W×D) | 114.5×50×17 mm / 4.5×2×0.7 inch | |
| Weight | 107 g (including battery) | |
| Languages | Czech, Danish, German, English, Spanish, French, Dutch, Polish, Russian, Swedish | |
| Operating systems | Microsoft Windows XP, Vista, 7 Mac OS X | |
| Recommended operating condition | 0-42°C / 32-107.6°F | |
| USB | Mini USB 2.0 | |
| USB classes | Composite / storage class | |
| Charging | Via AC adapter or USB | |
| SD cards | 512 MB up to 32 GB SD, SDHC | |
| Speaker (integrated) | Ø 23 mm / 0.9 inch, 256 mW | |
| Microphone size | Ø 10 mm / 0.4 inch | |
| Headphone jack | Stereo, 3.5 mm / 0.1 inch, 2 kΩ | |
| Microphone jack | Stereo, 3.5 mm / 0.1 inch, 8 kΩ | |
| Packaging Content Box | | |
| | SD card Li-ion battery USB cable Olympus Dictation Management Software CD Carrying case | Docking station AC adapter SD card Li-ion battery USB cable Olympus Dictation Managemant Software CD Carrying case |
| Available Accessories | | |
| Other | LI-42B Li-ion battery & LI-41C Charger for LI-42B Toshiba FlashAir™ Card RS32 Hand Controller for stand alone transcription or remote recording control A517 5V AC adapter AS-7000 PC Transcription Kit incl. RS31 Footswitch Further accessories at www.olympus-europa.com | |
| External microphones | ME51S Stereo microphone ME30W 2-channel microphone kit ME12 Noise-cancellation microphone ME15 Omnidirectional tie-clip microphone ME52W Unidirectional microphone TP8 Telephone pickup microphone, ME33 Boundary microphone | |

3 External stereo microphone necessary

Microsoft and Windows are registered trademarks of Microsoft Corporation. Macintosh is a trademark of Apple Inc. DragonNaturallySpeaking is a trademark of Nuance Communications, Inc. or its affiliates in the United States and/or other countries. SD, SDHC and SDHX logos are trademarks of SD-3C, LLC. FlashAir is a trademark of Toshiba Corporation. All other trademarks, product, brand and company names mentioned herein are the property of their respective owners. All rights reserved. Subject to changes in design and technology without notice.Latest specification and further accessories are available from www.olympus-europa.com

FIND YOUR LOCAL DEALER AT WWW.OLYMPUS.CO.UK/VOICE

Ask your local Olympus Dealer about thin client support in your particular environment.



OLYMPUS EUROPA SE & Co. KG
WWW.OLYMPUS-EUROPA.COM



Printed in Germany. 144P/12 - EN/EO475017 - online update 146PB 01 -

Olympus Professional Dictation Systems

DS-3500 / DS-7000

DS-3500
DS-7000

Said > Done

Generation Xcellence



The power of speech – easy, mobile and secure

At Olympus, we know how to make the most delicate of technology durable, mobile and reliable. And we understand the demands of professionals who need to use equipment in different environments and stressful situations and to easily integrate it in digital workflows. We have therefore combined our many years' experience in making professional high-tech equipment with our vast expertise in the field of digital recording, to develop the new DS-range.



While the previous ranges have excelled at making digital dictation reliable and easy to use, this new generation steps up to give you the perfect tools for fully integrated workflows. They are easily manageable and secure – and so mobile, you have the whole solution right in your pocket, whatever the challenges of the job.

Speech to Text

Easy-to-use design

Set-up, recording and editing is easier than ever on the new DS recorders. The DS-7000's slide switch makes dictation more comfortable than ever, dictation tags help simplify speech processing and the large colour LCD has been designed to be read in a blink of an eye.

Superior quality

Olympus' reputation for quality and reliability over 40 years speaks for itself – so no matter how hard you work, you can rest assured that your equipment can keep pace all the way.

Full flexibility

With their vast array of functions and accessories, audio codecs, up to 20 worktypes, long-lasting batteries and much more, the new DS devices can be customised to suit any purpose in any IT environment. Every feature is easily configurable with a separate software application.

Data security

Security is a key concern in any business. The new DS recorders can be secured with a 4-digit PIN and real-time 256-bit encryption while dictating, to give you full control over who knows what at any given moment.

Product Portfolio



DS-3500

- Easy operation via pushbuttons
- Full integration into professional workflows
- Perfect for recording conferences and interviews in stereo (with external microphones¹)



DS-7000

- Precision slide switch for full control in your palm
- Speech-optimised microphone
- Full integration into professional workflows
- Up to 200 customised selectable dictation tags

Product Overview³



System Chart

